

■ ステンレス溶接鋼管重量表

(単位：kg/4m)

B	A	肉厚(mm)		1.2	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.5	6.0	6.5
		外径(mm)												
1/8	6	10.5	1.11	1.34	1.69	1.99								
			1.12	1.35	1.70	2.00								
		12.7	1.38	1.67	2.13									
			1.38	1.68	2.14									
1/4	8	13.8	1.51	1.84	2.35	2.82	3.23							
			1.52	1.85	2.37	2.83	3.25							
		16.0	1.77	2.17	2.79									
			1.78	2.18	2.81									
3/8	10	17.3	1.92	2.36	3.05	3.69	4.28							
			1.94	2.38	3.07	3.71	4.32							
		19.0	2.13	2.62	3.39									
			2.14	2.63	3.41									
1/2	15	21.7	2.45	3.02	3.92	4.80	5.60							
			2.47	3.04	3.95	4.80	5.64							
		25.4	2.89	3.57	4.68	5.72	6.68							
			2.91	3.60	4.68	5.76	6.72							
3/4	20	27.2	3.11	3.84	5.04	6.16	7.24							
			3.13	3.86	5.04	6.20	7.28							
		32.0	3.68	4.56	5.96	7.36	8.68							
			3.71	4.60	6.00	7.40	8.72							
1	25	34.0	3.92	4.84	6.36	7.84	9.28	10.6	12.0					
			3.95	4.88	6.40	7.88	9.32	10.7	12.0					
		38.0	4.40	5.44	7.16	8.84	10.5	12.0	13.6					
			4.44	5.48	7.24	8.88	10.5	12.1	13.6					
1 1/4	32	42.7	4.96	6.16	8.12	10.0	11.9	13.7	15.4					
			5.00	6.20	8.16	10.1	12.0	13.8	15.5					
1 1/2	40	48.6	5.68	7.04	9.28	11.5	13.6	15.7	17.8					
			5.72	7.08	9.36	11.5	13.7	15.8	17.9					
		50.8	5.92	7.36	9.72	12.0	14.3	16.5	18.6					
			5.96	7.40	9.80	12.1	14.4	16.6	18.8					
2	50	60.5		8.80	11.6	14.4	17.2	19.9	22.5	27.6	30.2			
				8.88	11.7	14.6	17.3	20.0	22.7	27.8	30.3			
		63.5		9.28	12.2	15.2	18.1	20.9	23.7					
				9.32	12.3	15.3	18.2	21.0	23.9					
2 1/2	65	76.3		11.2	14.8	18.4	21.9	25.4	28.8	35.5	38.8	42.0		
				11.2	14.9	18.5	22.0	25.6	29.0	35.8	39.0	42.4		
3	80	89.1		13.1	17.4	21.6	25.7	29.8	33.9	42.0	46.0	49.6		
				13.2	17.5	21.7	25.9	30.0	34.1	42.0	46.0	50.0		
3 1/2	90	101.6		19.8	24.7	29.5	34.2	38.9	48.0			57.2		
				20.0	24.8	29.7	34.4	39.2	48.4			57.6		
4	100	114.3		22.4	27.8	33.3	38.6	44.0	54.4			64.8		
				22.5	28.0	33.5	38.9	44.4	54.8			65.2		
5	125	139.8		27.5	34.2	40.8	47.6	54.0	67.2			80.0	86.4	
				27.6	34.4	41.2	48.0	54.4	67.6			80.4	86.8	
6	150	165.2		32.5	40.4	48.4	56.4	64.4	80.0			95.2	103	
				32.7	40.8	48.8	56.8	64.8	80.4			95.6	104	
8	200	216.3					63.6		84.8	105		126	136	
							64.0		85.2	106		126	137	
10	250	267.4					79.2	92.0	105	131		156	169	
							79.6	92.8	106	132		157	170	
12	300	318.5					94.4		125	156		187	202	
							94.8		126	157		188	203	
14	350	355.6						140	175			209	226	
									141	176			210	228
16	400	406.4						160	200			239	259	
									162	201			241	261
18	450	457.2						181	225			270	292	
									182	227			272	294
20	500	508.0						201	250	275	300	325		
									202	252	277	302	327	
22	550	558.8						221	276	303	330	358		
									222	278	305	333	360	
24	600	609.6						241	301	331	361	391		
									243	303	333	363	393	

上段 SUS304、304L
下段 SUS316、316L